

To All Customers

Rep No. C25014a

September 11, 2026

Fuji Electric FA Components  
& Systems Co., Ltd.

**(Announcement of Product Discontinuation)**  
**Notification of Production Discontinuation of Some FC Series Magnetic Starters**

We would like to thank you for your continued patronage of Fuji products.

We are writing to announce the production discontinuation of some of our products.

Details are described below. Please review the following information and take appropriate actions.

Please also inform all related sections of your company of this discontinuation.

|                                    |                                                                                                                                                                                                                                                                                   |
|------------------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Product name                       | Magnetic starters                                                                                                                                                                                                                                                                 |
| Series name                        | FC Series                                                                                                                                                                                                                                                                         |
| Types                              | SF20BAAN-H11TSD (FW-1)<br>SF26BAAN-E11TVD (FW-1S)<br>SF26BAAN-M11TMD (FW-1S)<br>SF26BAAN-111TBD (FW-1S)<br>SF50BAAN-211TED (FW-3)<br>SF50BAAN-211TFD (FW-3)<br>SF50BAAN-211TGD (FW-3)<br>SF65BAAN-M11TJ (FW-4)                                                                    |
| Reason for discontinuation         | Due to decreasing demand, it has become difficult to provide a stable supply.                                                                                                                                                                                                     |
| Replacement models                 | SC-NEXT Series (for details, refer to the attachments)                                                                                                                                                                                                                            |
| Date of production discontinuation | September 30, 2026                                                                                                                                                                                                                                                                |
| Attachments                        | Attachment 1. FW-1 Comparison of Current and Replacement Products<br>Attachment 2. FW-1S Comparison of Current and Replacement Products<br>Attachment 3. FW-3 Comparison of Current and Replacement Products<br>Attachment 4. FW-4 Comparison of Current and Replacement Products |
| Maintenance parts                  | There are no maintenance parts.                                                                                                                                                                                                                                                   |
| Others                             | None                                                                                                                                                                                                                                                                              |

**(Attachment 1) FW-1 Comparison of Current and Replacement Products**

Rep No.C25014a

September 11, 2026

Fuji Electric FA Components &amp; Systems Co., Ltd.

|                                                  |                          | Current product (FW)                                                              | Replacement product (SC-NEXT)                                                                                                                          |
|--------------------------------------------------|--------------------------|-----------------------------------------------------------------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------|
| Product photo                                    |                          |  |                                                                     |
| Types                                            |                          | FW-1 (SF20BAA)                                                                    | SW18XA                                                                                                                                                 |
| Operating coil                                   |                          | AC                                                                                | AC                                                                                                                                                     |
| Rated operational current (A) 200 to 240 V, AC-3 |                          | 18 A                                                                              | 18 A                                                                                                                                                   |
| Auxiliary contact                                |                          | 2NO, 1NO+1NC, 2NC                                                                 | 1NO, 1NC*                                                                                                                                              |
| Thermal overload relay element count             |                          | 2,3                                                                               | 2,3                                                                                                                                                    |
| Thermal overload relay rating                    |                          | 4-8 A to 12-18 A                                                                  | 4-6 A to 15-18 A                                                                                                                                       |
| Ambient temperature                              |                          | -10°C to +50°C                                                                    | -10°C to +55°C                                                                                                                                         |
| Rated insulation voltage (V)                     |                          | 500 V                                                                             | 690 V                                                                                                                                                  |
| Electrical durability (AC-3)                     |                          | 250,000 operations                                                                | 1,500,000 operations                                                                                                                                   |
| Dimensions (mm)                                  | Width                    | 75                                                                                | 43                                                                                                                                                     |
|                                                  | Height                   | 108.5                                                                             | 125                                                                                                                                                    |
|                                                  | Depth                    | 85                                                                                | 78                                                                                                                                                     |
| Screw size                                       | Main terminal screw      | M4                                                                                | M3.5                                                                                                                                                   |
|                                                  | Auxiliary terminal screw | M3.5                                                                              | M3.5                                                                                                                                                   |
| Compatibility of mounting dimensions with FW     |                          | -                                                                                 | Not compatible                                                                                                                                         |
| Remarks                                          |                          | -                                                                                 | Ambient temperature, insulation voltage, and durability are higher than those of FW-1. Width and depth dimensions are also smaller than those of FW-1. |


\*2NO+1NC and 1NO+2NC are available as additional auxiliaries

**(Attachment 2) FW-1S Comparison of Current and Replacement Products**

Rep No.C25014a

September 11, 2026

Fuji Electric FA Components &amp; Systems Co., Ltd.

|                                                  |                          | Current product (FW)                                                              | Replacement product (SC-NEXT)                                                                                                                            |
|--------------------------------------------------|--------------------------|-----------------------------------------------------------------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------|
| Product photo                                    |                          |  |                                                                       |
| Types                                            |                          | FW-1S (SF26BAA)                                                                   | SW26XA                                                                                                                                                   |
| Operating coil                                   |                          | AC                                                                                | AC                                                                                                                                                       |
| Rated operational current (A) 200 to 240 V, AC-3 |                          | 26 A                                                                              | 26 A                                                                                                                                                     |
| Auxiliary contact                                |                          | 2NO, 1NO+1NC, 2NC                                                                 | 1NO, 1NC*                                                                                                                                                |
| Thermal overload relay element count             |                          | 2,3                                                                               | 2,3                                                                                                                                                      |
| Thermal overload relay rating                    |                          | 13-20 A to 20-26 A                                                                | 12-18 A to 20-26 A                                                                                                                                       |
| Ambient temperature                              |                          | -10°C to +50°C                                                                    | -10°C to +55°C                                                                                                                                           |
| Rated insulation voltage (V)                     |                          | 500 V                                                                             | 690 V                                                                                                                                                    |
| Electrical durability (AC-3)                     |                          | 250,000 operations                                                                | 2,000,000 operations                                                                                                                                     |
| Dimensions (mm)                                  | Width                    | 68                                                                                | 53                                                                                                                                                       |
|                                                  | Height                   | 121                                                                               | 130                                                                                                                                                      |
|                                                  | Depth                    | 90.5                                                                              | 82                                                                                                                                                       |
| Screw size                                       | Main terminal screw      | M4                                                                                | M4                                                                                                                                                       |
|                                                  | Auxiliary terminal screw | M3.5                                                                              | M3.5                                                                                                                                                     |
| Compatibility of mounting dimensions with FW     |                          | -                                                                                 | Not compatible                                                                                                                                           |
| Remarks                                          |                          | -                                                                                 | Ambient temperature, insulation voltage, and durability are higher than those of FW-1S. Width and depth dimensions are also smaller than those of FW-1S. |

\*2NO+1NC and 1NO+2NC are available as additional auxiliaries

**(Attachment 3) FW-3 Comparison of Current and Replacement Products**

Rep No.C25014a

September 11, 2026

Fuji Electric FA Components &amp; Systems Co., Ltd.

|                                                  |                          | Current product (FW)                                                              | Replacement product (SC-NEXT)                                                                                                                   |
|--------------------------------------------------|--------------------------|-----------------------------------------------------------------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------|
| Product photo                                    |                          |  |                                                              |
| Types                                            |                          | FW-3 (SF50BAA)                                                                    | SW50XA                                                                                                                                          |
| Operating coil                                   |                          | AC                                                                                | AC                                                                                                                                              |
| Rated operational current (A) 200 to 240 V, AC-3 |                          | 50 A                                                                              | 50 A                                                                                                                                            |
| Auxiliary contact                                |                          | 2NO, 1NO+1NC, 2NC                                                                 | 1NO+1NC*                                                                                                                                        |
| Thermal overload relay element count             |                          | 2,3                                                                               | 2,3                                                                                                                                             |
| Thermal overload relay rating                    |                          | 24-36 A to 34-50 A                                                                | 24-36 A to 44-54 A                                                                                                                              |
| Ambient temperature                              |                          | -10°C to +50°C                                                                    | -10°C to +55°C                                                                                                                                  |
| Rated insulation voltage (V)                     |                          | 500 V                                                                             | 690 V                                                                                                                                           |
| Electrical durability (AC-3)                     |                          | 250,000 operations                                                                | 2,000,000 operations                                                                                                                            |
| Dimensions (mm)                                  | Width                    | 78                                                                                | 64                                                                                                                                              |
|                                                  | Height                   | 138.5                                                                             | 148                                                                                                                                             |
|                                                  | Depth                    | 91.5                                                                              | 93                                                                                                                                              |
| Screw size                                       | Main terminal screw      | M5                                                                                | M5                                                                                                                                              |
|                                                  | Auxiliary terminal screw | M3.5                                                                              | M3.5                                                                                                                                            |
| Compatibility of mounting dimensions with FW     |                          | -                                                                                 | Not compatible                                                                                                                                  |
| Remarks                                          |                          | -                                                                                 | Ambient temperature, insulation voltage, and durability are higher than those of FW-3.<br>Width dimensions are also smaller than those of FW-3. |

\*2NO+2NC is available as an additional auxiliary

**(Attachment 4) FW-4 Comparison of Current and Replacement Products**

Rep No.C25014a

September 11, 2026

Fuji Electric FA Components &amp; Systems Co., Ltd.

|                                                  |                          | Current product (FW)                                                              | Replacement product (SC-NEXT)                                                                                                          |
|--------------------------------------------------|--------------------------|-----------------------------------------------------------------------------------|----------------------------------------------------------------------------------------------------------------------------------------|
| Product photo                                    |                          |  |                                                     |
| Types                                            |                          | FW-4 (SF65BAA)                                                                    | SW65XA                                                                                                                                 |
| Operating coil                                   |                          | AC                                                                                | AC                                                                                                                                     |
| Rated operational current (A) 200 to 240 V, AC-3 |                          | 65 A                                                                              | 65 A                                                                                                                                   |
| Auxiliary contact                                |                          | 2NO, 1NO+1NC, 2NC                                                                 | 1NO+1NC*                                                                                                                               |
| Thermal overload relay element count             |                          | 2,3                                                                               | 2,3                                                                                                                                    |
| Thermal overload relay rating                    |                          | 28-40 A to 45-67 A                                                                | 24-36 A to 53-65 A                                                                                                                     |
| Ambient temperature                              |                          | -10°C to +50°C                                                                    | -10°C to +55°C                                                                                                                         |
| Rated insulation voltage (V)                     |                          | 500 V                                                                             | 690 V                                                                                                                                  |
| Electrical durability (AC-3)                     |                          | 250,000 operations                                                                | 1,300,000 operations                                                                                                                   |
| Dimensions (mm)                                  | Width                    | 90                                                                                | 64                                                                                                                                     |
|                                                  | Height                   | 175                                                                               | 148                                                                                                                                    |
|                                                  | Depth                    | 109                                                                               | 93                                                                                                                                     |
| Screw size                                       | Main terminal screw      | M6                                                                                | M5                                                                                                                                     |
|                                                  | Auxiliary terminal screw | M3.5                                                                              | M3.5                                                                                                                                   |
| Compatibility of mounting dimensions with FW     |                          | -                                                                                 | Not compatible                                                                                                                         |
| Remarks                                          |                          | -                                                                                 | Ambient temperature, insulation voltage, and durability are higher than those of FW-4. Dimensions are also smaller than those of FW-4. |

\*2NO+2NC is available as an additional auxiliary